

DIN 94, Split pin, 10x56, ST, zinc-plated, standard, 5 µm, Zn5/An/T0



Article number	Weight in kg
2000941056	0.038
Customs number	Material
73182400	Steel
Quality	Coating
ST	zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter	Length
10 mm	56 mm



Product details

Norm DIN 94 wurde zurückgezogen und ist austauschbar mit ISO 1234

Lenght l1	20 mm
Material	Steel
Length	56 mm
Total lenght l	56 mm
Height h	16.6 mm
Norm	ISO 1234
Diameter	10 mm
Quality	ST
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Lenght l2	6.3 mm

Diameter d10 mm

Remarks

The nominal Ø of the split pin is also the nominal Ø of the associated split pin hole. For split pin holes up to nominal Ø 1,2 the recommended tolerance class is H 13 and from nominal Ø 1,6 the recommended tolerance class is H 14.

Standard was withdrawn. DIN corresponds to ISO 1234.

Product variants

Diameter (mm)	1	1,2	1,6	2	2,5	3,2	4	5	6,3	8	10	13	16
Length (mm)													
8	.												
10	.	.	.	.									
12	.		.	.	.								
14	.		.	.	.	.							
16	.		.	.	.	.							
18			.	.	.	.	.						
20	.		.	.	.	.	.	.					
22		.	.	.		.	.						
25			.	.	.	.	.	.					
28			.	.	.	.	.	.					
32	.		.	.	.	.	.	.	.				
36			.	.		.	.	.	.	.			
40				.	.	.	.	.	.	.			
45						.	.	.	.	.			
50				.	.	.	.	.	.	.	.		
56						.	.	.	.	.	.		
63					.	.	.	.	.	.	.		
71							.	.	.	.	.	.	
80							.	.	.	.	.	.	
90								.	.	.	.	.	
100								.	.	.	.	.	
112							.		.	.	.	.	
125									.	.	.	.	
140											.	.	
160												.	.
180													.
200													.