

DIN 94, Split pin, 6,3x125, ST, zinc-plated, standard, 5 µm, Zn5/An/T0



Article number 20009463125	Weight in kg 0.029
Customs number 73182400	Material Steel
Quality ST	Coating zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter 6,3 mm	Length 125 mm



Product details

Norm DIN 94 wurde zurückgezogen und ist austauschbar mit ISO 1234

Lenght l1	12.6 mm
Material	Steel
Length	125 mm
Total lenght l	125 mm
Height h	10.3 mm
Norm	ISO 1234
Diameter	6.3 mm
Quality	ST
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Lenght l2	4 mm

Diameter d6.3 mm

Remarks

The nominal Ø of the split pin is also the nominal Ø of the associated split pin hole. For split pin holes up to nominal Ø 1,2 the recommended tolerance class is H 13 and from nominal Ø 1,6 the recommended tolerance class is H 14.

Standard was withdrawn. DIN corresponds to ISO 1234.

Product variants

Diameter (mm)	1	1,2	1,6	2	2,5	3,2	4	5	6,3	8	10	13	16
Length (mm)													
8	•												
10	•	•	•	•									
12	•		•	•	•								
14	•		•	•	•	•							
16	•		•	•	•	•							
18			•	•	•	•	•						
20	•		•	•	•	•	•	•					
22		•	•	•		•	•						
25			•	•	•	•	•	•					
28			•	•	•	•	•	•					
32	•		•	•	•	•	•	•	•				
36			•	•		•	•	•	•	•			
40				•	•	•	•	•	•	•			
45						•	•	•	•	•			
50				•	•	•	•	•	•	•	•		
56						•	•	•	•	•	•		
63					•	•	•	•	•	•	•		
71							•	•	•	•	•	•	
80							•	•	•	•	•	•	
90								•	•	•	•	•	
100								•	•	•	•	•	
112							•		•	•	•	•	
125									•	•	•	•	
140											•	•	
160												•	•
180													•
200													•