

DIN 7981 C, Pan head sheet metal screw, ST 3,5x32, ST, zinc-plated, standard, 5 µm, Zn5/An/T0, TX 15



|                        |                                        |
|------------------------|----------------------------------------|
| Article number         | Weight in kg                           |
| 20798183532            | 0.002                                  |
| Customs number         | Material                               |
| 73181491               | Steel                                  |
| Quality                | Coating                                |
| ST                     | zinc-plated, standard, 5 µm, Zn5/An/T0 |
| Force application type | Diameter                               |
| Hexalobular internal   | 3,5 mm                                 |
| Length                 |                                        |
| 32 mm                  |                                        |



Product details

form C with cone end.

|                        |                                        |
|------------------------|----------------------------------------|
| Material               | Steel                                  |
| Force application type | Hexalobular internal                   |
| Length                 | 32 mm                                  |
| Total lenght l         | 32 mm                                  |
| Norm                   | DIN 7981 C                             |
| Diameter               | 3.5 mm                                 |
| Quality                | ST                                     |
| Height of the head k   | 2.6 mm                                 |
| Force application      | TX 15                                  |
| Coating                | zinc-plated, standard, 5 µm, Zn5/An/T0 |

|                         |        |
|-------------------------|--------|
| Diameter of the head dk | 6.9 mm |
| Diameter d              | 3.5 mm |

Remarks

Standard was withdrawn. DIN corresponds to ISO 14585. Changed head dimensions for ISO. Item is delivered according to DIN.

Product variants

| Diameter (mm) | 2,9 | 3,5 | 3,9 | 4,2 | 4,8 | 5,5 | 6,3 |
|---------------|-----|-----|-----|-----|-----|-----|-----|
| Length (mm)   |     |     |     |     |     |     |     |
| 6,5           | •   |     |     |     |     |     |     |
| 9,5           | •   | •   | •   | •   | •   |     |     |
| 13            | •   | •   | •   | •   | •   |     |     |
| 16            | •   | •   | •   | •   | •   |     |     |
| 19            | •   | •   | •   | •   | •   | •   | •   |
| 22            | •   | •   | •   | •   | •   |     |     |
| 25            | •   | •   | •   | •   | •   | •   | •   |
| 32            |     | •   | •   | •   | •   | •   | •   |
| 38            |     |     | •   | •   | •   | •   | •   |
| 45            |     | •   | •   |     | •   |     | •   |
| 50            |     | •   | •   | •   | •   | •   |     |
| 60            |     |     |     |     | •   |     | •   |
| 70            |     |     |     |     | •   | •   | •   |
| 80            |     |     |     |     | •   | •   | •   |
| 90            |     |     |     |     | •   | •   | •   |
| 100           |     |     |     |     | •   | •   | •   |