

DIN 912, cap screw, M 12x65, 8.8, zinc-plated, standard, 5 µm, Zn5/An/T0



Article number 2409121265	Weight in kg 0.068
Customs number 73181568	Material Steel
Quality 8.8	Coating zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter 12 mm	Length 65 mm

Product details

With hexagon socket.

Material	Steel
Depth t	6 mm
Total lenght l	65 mm
Length	65 mm
Norm	ISO 4762
Diameter	12 mm
Height of the head k	12 mm
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter of the head dk	18 mm
Thread length b	36 mm
Force application type	Hex socket
Quality	8.8

Force application	ISK 10
Diameter d	12 mm

Remarks

Standard was withdrawn. DIN similar to ISO 4762.

Product variants

Diameter (mm)	2,5	3	4	5	6	8	10	12	14	16	18	20	22	24	27	30	36	42	48
Length (mm)																			
4		.																	
5	.	.	.																
6		.	.	.	.														
8	.	.	.	.	.	.													
10	.	.	.	.	.	.	.												
12		.	.	.	.	.	.												
14		.	.	.	.	.	.	.											
16		.	.	.	.	.	.	.											
18		.	.	.	.	.	.	.											
20		.	.	.	.	.	.	.	.	.									
22		.	.	.	.	.	.	.											
25		.	.	.	.	.	.	.	.	.									
28					.		.	.											
30		.	.	.	.	.	.	.	.	.		.							
32				.															
35		.	.	.	.	.	.	.	.	.		.							
40		.	.	.	.	.	.	.	.	.	.	.		.		.			
45		.	.	.	.	.	.	.	.	.	.	.		.					
50		.	.	.	.	.	.	.	.	.		.		.					
55		.	.	.	.	.	.	.	.	.		.		.					
60		.	.	.	.	.	.	.	.	.		.		.	.	.			
65			.	.	.	.	.	.	.	.		.	.	.	.	.			
70			.	.	.	.	.	.	.	.	.	.	.	.	.	.			
75			.	.	.	.	.	.	.	.		.		.	.	.			
80			.	.	.	.	.	.	.	.		.		.	.	.			
85			.	.	.	.	.	.		.		.		.					
90			.	.	.	.	.	.	.	.	.	.		.	.	.			
95			.		.	.	.	.		.									
100			.	.	.	.	.	.	.	.		.		.	.	.	.		
105						.		.											
110			.	.	.	.	.	.	.	.	.	.		.	.	.	.	.	
115					.			.											
116					.														
120			.	.	.	.	.	.	.	.		.		.	.	.			
125							.												
130				.	.	.	.	.		.		.		.		.			
135				.	.	.													
140				.	.	.	.	.	.	.		.		.	.	.			
145						.	.												
150				.	.	.	.	.		.		.		.		.			.

Diameter (mm)	2,5	3	4	5	6	8	10	12	14	16	18	20	22	24	27	30	36	42	48
Length (mm)																			
155							.												
160				.	.	.	.	.	.	.		.		.		.	.	.	
170				.	.	.	.	.		.		.		.					
180				.	.	.	.	.	.	.		.		.	.	.	.		
185					.														
190					.		.			.		.		.					
200				.	.	.	.	.	.	.		.		.	.	.	.		
210						.		.		.		.							
220					.	.	.	.		.		.		.					
230							.			.				.		.			
240						.	.	.		.		.		.			.		
250						.						.							
260						.	.	.		.		.				.	.		
280						.	.	.		.		.		.					
290							.	.											
300						.	.	.		.		.		.	.				
350												.							
400																	.		