

DIN 931, hexagon head bolt, M 10x120, 8.8, zinc-plated, standard, 5 µm, Zn5/An/T0



|                               |                                                   |
|-------------------------------|---------------------------------------------------|
| Article number<br>24093110120 | Weight in kg<br>0.084                             |
| Customs number<br>73181588    | Diameter<br>10 mm                                 |
| Length<br>120 mm              | Material<br>Steel                                 |
| Quality<br>8.8                | Coating<br>zinc-plated, standard, 5 µm, Zn5/An/T0 |
| Force application<br>SW 17    | Norm<br>DIN 931                                   |



Product details

ISO 4014.

|                        |                                        |
|------------------------|----------------------------------------|
| Material               | Steel                                  |
| Total lenght l         | 120 mm                                 |
| Length                 | 120 mm                                 |
| Norm                   | DIN 931                                |
| Diameter               | 10 mm                                  |
| Height of the head k   | 6.4 mm                                 |
| Coating                | zinc-plated, standard, 5 µm, Zn5/An/T0 |
| Thread length b        | 26 mm                                  |
| Force application type | External hex                           |
| Norm                   | DIN 931                                |

|                   |       |
|-------------------|-------|
| Quality           | 8.8   |
| Force application | SW 17 |
| Diameter d        | 10 mm |

Remarks

Changed SW for ISO. M 10, M 12, M 14 and M 22 only available according to DIN 931. For further sizes see ISO 4014.

Application

Universell einsetzbar, vor allem im Maschinenbereich

Product variants

| Force application | SW 16 | SW 17 |
|-------------------|-------|-------|
| Norm              |       |       |
| DIN 931           |       | •     |
| ISO 4014          | •     |       |