

ISO 4014 / DIN 931, hexagon head bolt, M 20x90, 8.8, zinc-plated, standard, 5 µm, Zn5/An/T0



|                   |                                        |
|-------------------|----------------------------------------|
| Article number    | Weight in kg                           |
| 2409312090        | 0.279                                  |
| Customs number    | Diameter                               |
| 73181588          | 20 mm                                  |
| Length            | Material                               |
| 90 mm             | Steel                                  |
| Quality           | Coating                                |
| 8.8               | zinc-plated, standard, 5 µm, Zn5/An/T0 |
| Force application | Norm                                   |
| SW 30             | ISO 4014 / DIN 931                     |



Product details

ISO 4014.

|                        |                                        |
|------------------------|----------------------------------------|
| Material               | Steel                                  |
| Total lenght l         | 90 mm                                  |
| Length                 | 90 mm                                  |
| Norm                   | ISO 4014                               |
| Diameter               | 20 mm                                  |
| Height of the head k   | 12.5 mm                                |
| Coating                | zinc-plated, standard, 5 µm, Zn5/An/T0 |
| Thread length b        | 46 mm                                  |
| Force application type | External hex                           |
| Norm                   | ISO 4014 / DIN 931                     |

|                   |       |
|-------------------|-------|
| Quality           | 8.8   |
| Force application | SW 30 |
| Diameter d        | 20 mm |

Remarks

Changed SW for ISO. M 10, M 12, M 14 and M 22 only available according to DIN 931. For further sizes see ISO 4014.

Application

Universell einsetzbar, vor allem im Maschinenbereich

Product variants

|                    |       |
|--------------------|-------|
| Force application  | SW 30 |
| Norm               |       |
| ISO 4014 / DIN 931 | .     |