

DIN 125 A, Washer, 12, 140 HV, zinc-plated, thick layer, 8 µm, Zn8/Cn/T2 µ0,12 - 0,18



Article number 40600125813	Weight in kg 0.006
Customs number 73182200	Material Steel
Quality 140 HV	Coating zinc-plated, thick layer, 8 µm, Zn8/Cn/T2 µ0,12 - 0,18
Suitable for screw diameter M 12	Inner diameter 13 mm
Outer diameter 24 mm	Thickness 2,5 mm
Norm DIN 125 A	



Product details

Form A ohne Fase. DIN 125-A wurde zurückgezogen und ist austauschbar mit ISO 7089. Abmessung nach ISO Norm, der Nenndurchmesser entspricht dem Schraubendurchmesser, für den die Scheibe geeignet ist.

Outer diameter	24 mm
Thickness	2.5 mm
Material	Steel
Suitable for screw diameter	M 12
Inner diameter	13 mm
Norm	DIN 125 A
Norm	DIN 125 A

Quality	140 HV
Coating	zinc-plated, thick layer, 8 µm, Zn8/Cn/T2 µ0,12 - 0,18
Diameter d2	24 mm
Thickness s	2.5 mm
Diameter d1	13 mm

Remarks

Standard was withdrawn. DIN similar to ISO 7089. Hardness changed.

Product variants

Thickness (mm)	2,5
Norm	
DIN 125 A	.