ISO 15977 FAKKT blind rivet, dome head, 3x8, AL/ST, CR: 3,5-5

Article number
580000110330080

Weight in kg
0.001

Customs number
83082000

Coating
pln

Clamping range min.
3,5 mm

Clamping range max.
5 mm

Diameter
3 mm

Length
8 mm

Product details

Material	Aluminum
Length	8 mm
Lenght of rivet mandrel p	26 mm
Norm	ISO 15977
Tensile force	800 N
Diameter	3 mm
Height of the head k	1 mm
Bore hole diameter	3,1 mm
Coating	pln
Diameter of the head dk	6.3 mm
Head type	dome head
Clamping range max.	5 mm
Clamping range min.	3.5 mm
Shear force	500 N

Keller & Kalmbach GmbH • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com

www.keller-kalmbach.de

Diameter of rivet mandrel dm	1.7 mm
Material mandrel	Steel
Quality	AL/ST
Lenght of rivet sleeve l	8 mm
Material sleeve	Aluminium
Diameter d	3 mm

Remarks

Standard DIN 7337 A was withdrawn. DIN similar to DIN EN ISO 15977.

Product variants

Diameter (mm)	3	3,2
Length (mm)		
8	•	•

Keller & Kalmbach GmbH • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com

www.keller-kalmbach.de